

6' SINGLE AXLE SPECIFICATIONS 3500# Axle

	ATW610SA	ATW612SA	ATW614SA
OVERALL LENGTH	14' 4"	16' 4"	18' 4"
" WIDTH	7' 9"	7' 9"	7' 9"
" HEIGHT	7' 7"	7' 7"	7' 7"
INTERIOR LENGTH	11' 11"	13' 11"	15' 11"
" WIDTH	5' 8½"	5' 8½"	5' 8½"
" HEIGHT	6' 1½"	6' 1½"	6' 1½"
REAR DOOR(S)	DOUBLE	DOUBLE	DOUBLE
" " WIDTH	4' 11"	4' 11"	4' 11"
" " HEIGHT	5' 5½"	5' 5½"	5' 5½"
HITCH WEIGHT	220 lbs.	240 lbs.	260 lbs. *
" HEIGHT	16"	16"	16"
BALL SIZE	2"	2"	2"
PLATFORM HEIGHT	15"	15"	15"
G.V.W.R.	2990 lbs.	2990 lbs.	2990 lbs.
CURB WEIGHT	1495 lbs.	1650 lbs.	1800 lbs. *
PAYLOAD CAPACITY	1495 lbs.	1340 lbs.	1190 lbs. *
AXLE	2990 lbs.	2990 lbs.	2990 lbs.
TIRES	ST205/75R15	ST205/75R15	ST205/75R15
WHEELS	5 BOLT	5 BOLT	5 BOLT
FRAME	3" TUBE	3" TUBE	3" TUBE
FLOOR (24"O/C)	3/4" PLYWOOD	3/4" PLYWOOD	3/4" PLYWOOD
SIDE WALLS (16"O/C)	3/8" PLYWOOD	3/8" PLYWOOD	3/8" PLYWOOD

STANDARD FEATURES

RUBBER TORSION AXLES
 E-Z LUBE HUBS w/GREASE CAPS
 PREMIUM RADIAL TIRES
 WHITE MODULAR WHEELS
 S.STEEL CENTER CAPS
 WELDED SAFETY CHAINS
 CAMLOCK DOOR LATCHS
 TRIPLE WEDGE FRONT END
 040 SMOOTH EXTERIOR ALUMINUM
 ONE PIECE ROLLED ROOF

ELECTRIC BRAKES
 12 VOLT BREAK A WAY SWITCH w/BATTERY
 FORMED REAR STEEL HEADER
 INTERIOR WIRING
 DOUBLE SEALED SIDE AND REAR DOOR(S)
 ALUMINUM FENDERS
 MORE CARGO CAPACITY
 HIGH TENSIL "I" BEAM CROSS MEMBERS
 UNDERCOATED FLOOR & CHASSIS

March, 2008