

7' TANDEM AXLE SPECIFICATIONS 5200# Axles

	ATW712TA3	ATW714TA3	ATW716TA3	ATW718TA3
OVERALL LENGTH	16' 10"	18' 10"	20' 10"	22' 10"
" WIDTH	8' 6"	8' 6"	8' 6"	8' 6"
" HEIGHT	8' 4"	8' 4"	8' 4"	8' 4"
INTERIOR LENGTH	14' 2"	16' 2"	18' 2"	20' 2"
" WIDTH	6' 9"	6' 9"	6' 9"	6' 9"
" HEIGHT	6' 8"	6' 8"	6' 8"	6' 8"
REAR DOOR(S)	DOUBLE	DOUBLE	DOUBLE	DOUBLE
" " WIDTH	6' 3"	6' 3"	6' 3"	6' 3"
" " HEIGHT	5' 11"	5' 11"	5' 11"	5' 11"
HITCH WEIGHT	325 lbs.	350 lbs.	375 lbs.	400 lbs.
" HEIGHT	18"	18"	18"	18"
BALL SIZE	2 5/16"	2 5/16"	2 5/16"	2 5/16"
PLATFORM HEIGHT	19"	19"	19"	19"
G.A.W.R.	9990 lbs.	9990 lbs.	9990 lbs.	9990 lbs.
G.V.W.R.	9990 lbs.	9990 lbs.	9990 lbs.	9990 lbs.
CURB WEIGHT	1990 lbs. *	2180 lbs. *	2570 lbs. *	2960 lbs. *
PAYLOAD CAPACITY	8000 lbs. *	7810 lbs. *	7420 lbs. *	7030 lbs. *
AXLE (TANDEM)	5200 lbs.	5200 lbs.	5200 lbs.	5200 lbs.
BRAKES	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC
TIRES	ST225/75R15	ST225/75R15	ST225/75R15	ST225/75R15
WHEELS	6 BOLT	6 BOLT	6 BOLT	6 BOLT
FRAME	6" TUBE	6" TUBE	6" TUBE	6" TUBE
FLOOR (24"O/C)	3/4" PLYWOOD	3/4" PLYWOOD	3/4" PLYWOOD	3/4" PLYWOOD
SIDE WALLS (16"O/C)	3/8" PLYWOOD	3/8" PLYWOOD	3/8" PLYWOOD	3/8" PLYWOOD

STANDARD FEATURES

RUBBER TORSION AXLES	ALL-WHEEL ELECTRIC BRAKES
E-Z LUBE HUBS w/GREASE CAPS	12 VOLT BREAKAWAY SWITCH w/BATTERY
PREMIUM RADIAL TIRES	FORMED REAR STEEL HEADER
WHITE MODULAR WHEELS	INTERIOR WIRING
S.STEEL CENTER CAPS	DOUBLE SEALED SIDE AND REAR DOOR(S)
WELDED SAFETY CHAINS	ALUMINUM FENDERS
CAMLOCK DOOR LATCHS	MORE CARGO CAPACITY
TRIPLE WEDGE FRONT END	HIGH TENSIL "I" BEAM CROSS MEMBERS
040 SMOOTH EXT. ALUMINUM	UNDERCOATED FLOOR & CHASSIS
ONE PIECE ROLLED ROOF	

March, 2010