

8' TANDEM AXLE SPECIFICATIONS 3500# Axles

	ATW816TA2	ATW818TA2	ATW820TA2	ATW822TA2	ATW824TA2
OVERALL LENGTH	21' 2"	23' 2"	25' 2"	27' 2"	29' 2"
" WIDTH	8' 5"	8' 5"	8' 5"	8' 5"	8' 5"
" HEIGHT	8' 5"	8' 5"	8' 5"	8' 5"	8' 5"
INTERIOR LENGTH	18' 2"	20' 2"	22' 2"	24' 2"	26' 2"
" WIDTH	7' 8½"	7' 8½"	7' 8½"	7' 8½"	7' 8½"
" HEIGHT	6' 8"	6' 8"	6' 8"	6' 8"	6' 8"
REAR DOOR(S)	DOUBLE	DOUBLE	DOUBLE	DOUBLE	DOUBLE
" " WIDTH	7' 3"	7' 3"	7' 3"	7' 3"	7' 3"
" " HEIGHT	5' 11"	5' 11"	5' 11"	5' 11"	5' 11"
HITCH WEIGHT	515 lbs. *	535 lbs. *	550 lbs. *	565 lbs. *	580lbs. *
" HEIGHT	18"	18"	18"	18"	18"
BALL SIZE	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
PLATFORM HEIGHT	19"	19"	19"	19"	19"
G.A.W.R.	7000 lbs.	7000 lbs.	7000 lbs.	7000 lbs.	7000 lbs.
G.V.W.R.	7000 lbs.	7000 lbs.	7000 lbs.	7000 lbs.	7000 lbs.
CURB WEIGHT	2625 lbs.	2875 lbs. *	3125 lbs.	3375 lbs. *	3625 lbs.
PAYLOAD CAPACITY	4375 lbs.	4125 lbs. *	3875 lbs.	3625 lbs. *	3375 lbs.
AXLE (TANDEM)	3500 lbs.	3500 lbs.	3500 lbs.	3500 lbs.	3500 lbs.
BRAKES	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC
TIRES	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15
WHEELS	5 BOLT	5 BOLT	5 BOLT	5 BOLT	5 BOLT
FRAME	6" TUBE	6" TUBE	6" TUBE	6" TUBE	6" TUBE
FLOOR (24"O/C)	3/4" PLYWOOD	3/4" PLYWOOD	3/4" PLYWOOD	3/4" PLYWOOD	3/4" PLYWOOD
SIDE WALLS (16"O/C)	3/8" PLYWOOD	3/8" PLYWOOD	3/8" PLYWOOD	3/8" PLYWOOD	3/8" PLYWOOD

STANDARD FEATURES

RUBBER TORSION AXLES	ALL-WHEEL ELECTRIC BRAKES
E-Z LUBE HUBS	12 VOLT BREAKAWAY SWITCH w/BATTERY
PREMIUM RADIAL TIRES	FORMED REAR STEEL HEADER
WHITE MODULAR WHEELS	INTERIOR WIRING
S.STEEL CENTER CAPS	DOUBLE SEALED SIDE AND REAR DOOR(S)
WELDED SAFETY CHAINS	ALUMINUM FENDERS
CAMLOCK DOOR LATCHES	MORE CARGO CAPACITY
TRIPLE WEDGE FRONT END	HIGH TENSIL "I" BEAM CROSS MEMBERS
040 EXTERIOR ALUMINUM	UNDERCOATED FLOOR & CHASSIS
ONE PIECE ROLLED ROOF	

March, 2008