

8' TANDEM AXLE SPECIFICATIONS 6000# Axles

	ATW816TA4	ATW818TA4	ATW820TA4	ATW822TA4	ATW824TA4
OVERALL LENGTH	21' 2"	23' 2"	25' 2"	27' 2"	29' 2"
" WIDTH	8' 5"	8' 5"	8' 5"	8' 5"	8' 5"
" HEIGHT	8' 5"	8' 5"	8' 5"	8' 5"	8' 5"
INTERIOR LENGTH	18' 2"	20' 2"	22' 2"	24' 2"	26' 2"
" WIDTH	7' 8½"	7' 8½"	7' 8½"	7' 8½"	7' 8½"
" HEIGHT	6' 8"	6' 8"	6' 8"	6' 8"	6' 8"
REAR DOOR(S)	DOUBLE	DOUBLE	DOUBLE	DOUBLE	DOUBLE
" " WIDTH	7' 3"	7' 3"	7' 3"	7' 3"	7' 3"
" " HEIGHT	5' 11"	5' 11"	5' 11"	5' 11"	5' 11"
HITCH WEIGHT	420 lbs.	440 lbs. *	460 lbs. *	480 lbs. *	500 lbs. *
" HEIGHT	18"	18"	18"	18"	18"
BALL SIZE	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
PLATFORM HEIGHT	19"	19"	19"	19"	19"
G.A.W.R.	6,000 lbs.	6,000 lbs.	6,000 lbs.	6,000 lbs.	6,000 lbs.
G.V.W.R.	12,000 lbs.	12,000 lbs.	12,000 lbs.	12,000 lbs.	12,000 lbs.
CURB WEIGHT	2900 lbs.	3100 lbs. *	3300 lbs.	3500 lbs.	3700 lbs.
PAYLOAD CAPACITY	9100 lbs.	8900 lbs.	8700 lbs.	8500 lbs.	8300 lbs.
AXLE (TANDEM)	6,000 lbs.	6,000 lbs.	6,000 lbs.	6,000 lbs.	6,000 lbs.
BRAKES	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC
TIRES	ST235/80R16	ST235/80R16	ST235/80R16	ST235/80R16	ST235/80R16
WHEELS	8 BOLT	8 BOLT	8 BOLT	8 BOLT	8 BOLT
FRAME	6" TUBE	6" TUBE	6" TUBE	6" TUBE	6" TUBE
FLOOR (24"O/C)	3/4" PLYWOOD	3/4" PLYWOOD	3/4" PLYWOOD	3/4" PLYWOOD	3/4" PLYWOOD
SIDE WALLS (16"O/C)	3/8" PLYWOOD	3/8" PLYWOOD	3/8" PLYWOOD	3/8" PLYWOOD	3/8" PLYWOOD

STANDARD FEATURES

RUBBER TORSION AXLES ALL-WHEEL ELECTRIC BRAKES
 INTERIOR WIRING 12 VOLT BREAKAWAY SWITCH w/BATTERY
 PREMIUM RADIAL TIRES FORMED REAR STEEL HEADER
 WHITE MODULAR WHEELS E-Z LUBE HUBS w/GREASE CAPS
 S.STEEL CENTER CAPS DOUBLE SEALED SIDE AND REAR DOOR(S)
 WELDED SAFETY CHAINS TRIPLE WEDGE FRONT END
 CAMLOCK DOOR LATCHES MORE CARGO CAPACITY
 ALUMINUM FENDERS HIGH TENSIL "I" BEAM CROSS MEMBERS
 .040 EXTERIOR ALUMINUM UNDERCOATED FLOOR & CHASSIS
 ONE PIECE ROLLED ROOF

March, 2008